

Mini Remote Control



TDS12501

The TDS12501 is a small and user friendly infra-red remote control for home automation control. The controlled functions adapt automatically according the touch panel or interface to which the infrared remote control is communicating. (button 1 controls function 1 of the TELETASK interface which receives the IR code)

APPLICATION

To be used where remote control of the functions on a touch panel or other TELETASK interface with infrared receiver is desired.

CHARACTERISTICS

The remote control is equipped with 8 buttons for the control of 8 functions; the controlled function depends on the TELETASK interface that receives the IR command.

Shift button 'arrow': pressed in combination with the 8 numeric buttons it controls 8 extra functions (right group of 8 buttons on LATUS)

Shift button 'house': pressed in combination with the 8 numeric buttons it controls the 8 "MASTER" functions.

Battery

 $\mbox{CR2025}$ (3V Lithium) – supplied with the unit. Compatible with CR2032

SETTINGS

IR functions via PROSOFT

POWER CONSUMPTION

Estimated battery lifetime: 1 year (no warranty on the battery)

DIMENSIONS

33 W x 86 H x 7 D (mm)

NET | GROSS WEIGHT 0,015 kg | 0,050 kg

PACKAGING CONTENT

TDS12501

STORAGE

Temperature

-20°C to +65°C

Relative humidity

15% to 85%

IP PROTECTION RATE

OPERATING RANGE

Temperature 0°C to +50°C max.

Relative humidity

5% to 80% at 25°C (non-condensing ambient)

©, TELETASK, GENT, 2016

TELETASK can't be responsible for potential errors in the data sheets and technical documentation. Changes in the product features can be made at any time, without prior notice